



NOTE: ALL LEADS 9" OUT MIN., STRIPPED .5"



HAMMOND MANUFACTURING
PWDP13025

PRIMARY BLK - WHT 1-2: 120V 60HZ
 SEC 1 RED-RED/WHT-RED 3-4-5: 960VCT @0.20A
 SEC 2 BLK-BLK/WHT-BLK 6-7-8: 560VCT @0.10A
 SEC 3 GRN-GRN/WHT-GRN 9-10-11: 6.3VCT @9.0A
 SEC 4 WHT-WHT/BLK-WHT 12-13-14: 5.0VCT @3.0A
 SEC 5 YEL-YEL/BLK-YEL 15-16-17: 2.5VCT @10.0A

DATE _____ MADE IN CANADA

DIMENSIONS:	
A	4.375" ±0.063
B	4.846" ±0.125
C	5.298" ±0.063
D	3.500" ±0.063
E	3.250" ±0.063
G	0.281" x 0.625" ±0.015

ELECTRICAL DATA:		
TESTS	CONDITIONS	ACCEPTANCE CRITERIA
SEC N.L.V.	@120V BLK - WHT	
	RED - RED =	1000V ±2%
	BLK - BLK =	584V ±2%
	GRN - GRN =	6.52V ±5%
	WHT - WHT =	5.20V ±5%
	YEL - YEL =	2.60V ±5%
DCR	BLK - WHT =	0.81 ±20%
IN OHMS	RED - RED =	124.4 ±20%
	BLK - BLK =	150.3 ±20%
	GRN - GRN =	0.020 ±20%
	WHT - WHT =	0.010 ±20%
	YEL - YEL =	0.030 ±20%
HIPOT	PRIMARY - CORE	2000V, 60Hz, 1 SEC
	SEC #1,2 - CORE	3200V, 60Hz, 1 SEC
	SEC #3,5 - CORE	1000V, 60Hz, 1 SEC
	SEC #4 - CORE	7000V, 60Hz, 1 SEC
	PRI - SEC #1,2	3200V, 60Hz, 1 SEC
	PRI - SEC #3,5	1000V, 60Hz, 1 SEC
	PRI - SEC #4	7000V, 60Hz, 1 SEC
	SEC #4 - SEC #1,2,3,5	7000V, 60Hz, 1 SEC
	SEC #1 - SEC #2,3,5	3200V, 60Hz, 1 SEC
	SEC #2 - SEC #3,5	2500V, 60Hz, 1 SEC
	SEC #3 - SEC #5	1000V, 60Hz, 1 SEC

PROPERTY AND COPYRIGHT NOTICE

THIS DRAWING AND THE INFORMATION IT CONVEYS ARE THE PROPERTY OF HAMMOND MANUFACTURING. IT MAY NOT BE REPRODUCED, TRANSMITTED OR USED IN ANY MANNER WHATSOEVER WITHOUT THE WRITTEN PERMISSION OF HAMMOND MANUFACTURING.

REV	NOTES	BY	DATE	REV	NOTES	BY	DATE
1	CORRECTED DIMENSION TABLE	CB	05/07/14				

HAMMOND MANUFACTURING ELECTRONIC DIVISION
 52 RANKIN PLACE,
 WATERLOO, ONTARIO, N2J 3Z5
 PHONE: 519.886.6181 FAX: 519.886.9540

EDB PWDP13025

DRAWN CBACIK	DATE 04/24/14	NUMBER PWDP13025
APPROVED	DATE	